

Product Information

www.vdo.com

Viewline Mechanical Water Pressure Gauge

Description

Gauge to indicate cooling-water pressure.



Picture:
Mechanical Water Pressure Gauge

Features

- LED illumination
- Backlit technology
- Changeable bezels
- Antifog and splash protection
- Panel and flush mount possibility

Concept

Housing	Polycarbonat (PC)
Bezel	PC (black, white) or ABS (chrome); different colors and shapes (see accessories)
Lens	PMMA; double lens
Dial	different colors (black, white)
Pointer	backlit, white on black dials; red on white dials
Illumination	backlit
	Dial: LED amber (605nm)
Warning LED	Pointer: LED red (632nm)
Mounting	red (632nm), adjustable via LCD display or optional PC software
	Spinlock Nut; locking height 0.5mm – 20mm,
Connection	Optional Studs and Bracket; locking height 2 – 13mm
	8-pole MQS connector system

Technical Data		
Installation depth	60mm	
Installation diameter	52mm	
Tube diameter	3.6 mm (inner)	
Deflection angle	270°	
Operating Voltage	10 – 16 Volt	
Accuracy	< ± 0.15 bar	
Current consumption	< 35 mA	
Operating temperature	-40°C to +85°C; plated bezels (chrome) -30°C to +70°C	
Storage temperature	-40°C to +85°C to 48h; plated bezels (chrome) -40°C to +70°C +90°C for 1h	
Temperature shock	Range Transformation time Retention time	-40°C to +85°C; plated bezels (chrome) -40°C to +70°C 10 seconds 2h
Climatic test	Range Rel. Humidity	+25°C to +55°C 95%
Vibration	Sinus 2g; 10-500Hz; duration 16h Noise 3g; 10-1000Hz, duration 8h	
Mechanical shock	continuous Single shock Free fall	25g; 6ms; 1Hz 100g; 11ms 1m; 3 times
Chemical resistance against	<ul style="list-style-type: none"> - preservative agent - preservative agent remover - cold cleaner - methylated spirit - interior cleaner - drinks containing caffeine and tannin 	
Nominal position	NL 0 to NL 85 (DIN16257)	
Protection class	according to IEC 60529 Front: IP67 (in nominal position) Rear: IP52 (in nominal position)	

Available Gauges:

No. unpacked *	Dial color	Diameter [mm]	Double scale	Measurement range	ISO Symbol	Sensor	Double lens
A2C31233300	black	52mm	yes	0 - 2 bar 0 – 30 psi		Water pressure	yes
A2C31233400	white	52mm	yes	0 - 2 bar 0 – 30 psi		Water pressure	yes

* "No. unpacked" is not a order number

Accessories:

A2C59510854	VL Mounting Kit (studs and brackets) 52, 85, 110mm
A2C59510864	VL Mounting bracket flush mount
A2C53215640	VL Sealing Ring 52mm flush mount
A2C59510847	Bush housing, 8-pin
A2C53324664	Protective connector cap, 8-pin
Tyco Nr. 539635-1	Hand pliers
Tyco Nr. 539682-2	Tool for hand pliers.
Tyco Nr. 1355718-1	Single contacts 0.14 – 0.22 mm ² tin plated
Tyco Nr. 963729-1	Single contacts 0.5 – 0.75 mm ² tin plated
Tyco Nr. 1355717-1	Strip 0.14 – 0.22 mm ² tin plated
Tyco Nr. 928999-1	Strip 0.25 – 0.5 mm ² tin plated
Tyco Nr. 963715-1	Strip 0.5 – 0.75 mm ² tin plated

Bezels 52mm

	Black	Chrome	White
Flat	A2C53186040	A2C53186023	A2C53186022
Round	A2C53186027	A2C53186029	A2C53186028
Triangle	A2C53186024	A2C53186026	A2C53186025